



HAUSSMANN
NATURAL STONE

Noir Sully

Origin : Belgium

Physical properties			Class
Apparent density (ASTM C97)	Kg/m3	2687	III
Absorption coefficient (ASTM C97)	%	0.11	III
Porosity	%	0.28	
Compressive strength (ASTM 170)	MPa	157.9	III
Modulus of rupture (ASTM C99)	MPa	16.7	III
Flexural strength (ASTM C880)	%	2.87	
Abrasion (Hd) (ASTM C241)	mm		
Resistance to fixation elements (3cm)	MPa		
Bending strength	MPa		
Freeze thaw	Cycles	>240	
Bent Bolt Anchor Pullout test (ASTM C1354)	mm		
Pin Clip anchor Pullout test (ASTM C1354)	mm		

Recommended Uses			
Applications		Traffic wear	
Cladding	x	Not a flooring material	
Exterior pavers	x	Heavy commercial (mall)	x
Interior floors	x	Low commercial (office)	x
Kitchen counters		Residential	x
Other counters	x		
Wet areas	x		

Finishes Available			
Honed	x	Dalle Rustique	
Flamed	x	Bush-Hammered	x
Polished	x	Tumbled	x
Antique		Iron or sand Blasted	
Patiné	x	Split-Face	
Leather (flamed-brushed)		Sawn	
Medieval	x		
Linen			

Production data		
Maximum project size	sqft	50,000
Slab size	inch	98"x54"
Thickness Min	inch	3/8"
Thickness Max	inch	6"