



## Albi

**Origin :** Spain

| Physical properties                        |        |      | Class |
|--|--------|------|-------|
| Apparent density (ASTM C97)                | Kg/m3  | 2320 | II    |
| Absorption coefficient (ASTM C97)          | %      | 4.8  | II    |
| Porosity                                   | %      | 16.3 |       |
| Compressive strength (ASTM 170)            | MPa    |      |       |
| Modulus of rupture (ASTM C99)              | MPa    |      |       |
| Flexural strength (ASTM C880)              | %      | 6.5  |       |
| Abrasion (Hd) (ASTM C241)                  | mm     | 31   |       |
| Resistance to fixation elements (3cm)      | MPa    |      |       |
| Bending strength                           | MPa    |      |       |
| Freeze thaw                                | Cycles |      |       |
| Bent Bolt Anchor Pullout test (ASTM C1354) | mm     |      |       |
| Pin Clip anchor Pullout test (ASTM C1354)  | mm     |      |       |

| Recommended Uses |   |                         |   |
|------------------|---|-------------------------|---|
| Applications     |   | Traffic wear            |   |
| Cladding         | x | Not a flooring material |   |
| Exterior pavers  | x | Heavy commercial (mall) |   |
| Interior floors  | x | Low commercial (office) | x |
| Kitchen counters |   | Residential             | x |
| Other counters   | x |                         |   |
| Wet areas        | x |                         |   |

| Finishes Available       |   |                      |   |
|--------------------------|---|----------------------|---|
| Honed                    | x | Dalle Rustique       |   |
| Flamed                   |   | Bush-Hammered        |   |
| Polished                 |   | Tumbled              |   |
| Antique                  |   | Iron or sand Blasted |   |
| Patiné                   | x | Split-Face           | x |
| Leather (flamed-brushed) |   | Sawn                 |   |
| Medieval                 |   |                      |   |
| Linen                    |   |                      |   |

| Production data      |      |          |  |
|----------------------|------|----------|--|
| Maximum project size | sqft | 100,000  |  |
| Slab size            | inch | 100"x56" |  |
| Thickness Min        | inch | 3/8"     |  |
| Thickness Max        | inch | 6"       |  |