



## Parfeuille

**Origin :** France  
**Nature :** Antique

Physical properties			Class
Apparent density (ASTM C97)	Kg/m3		N/A
Absorption coefficient (ASTM C97)	%		N/A
Porosity	%		N/A
Compressive strength (ASTM 170)	MPa		N/A
Modulus of rupture (ASTM C99)	MPa		
Flexural strength (ASTM C880)	MPa		N/A
Abrasion (Hd) (ASTM C241)	mm		N/A
Resistance to fixation elements (3cm)	MPa		
Bending strength	MPa		
Freeze thaw	Cycles		
Bent Bolt Anchor Pullout test (ASTM C1354)	mm		
Pin Clip anchor Pullout test (ASTM C1354)	mm		

Recommended Uses			
Applications		Traffic wear	
Cladding	x	Not a flooring material	
Exterior pavers	x	Heavy commercial (mall)	
Interior floors	x	Low commercial (office)	x
Kitchen counters		Residential	x
Other counters			
Wet areas	x		

Finishes Available s = stock, c = Custom			
Honed		Linen	
Antique	s	Micro Bush-hammered	
Bamboo		Old world	
Bush-hammered		Patiné	
Dalle Rustique		Polished	
Elektron		Sawn	
Flamed		Split-Face	
Iron or sand Blasted		Tooled	
Leather (flamed-brushed)		Tumbled	

Production data		
Maximum project size	sqft	200,000
Slab size	inch	N/A
Thickness Min	inch	1"
Thickness Max	inch	1-1/4"